

Changes to the third edition following December 2009 update

Section Page Amendment

Introduction

Table 1	2	New robust details E-WM-19 and E-WT-4 added.
Table 2	3	New robust detail E-FC-12 added.
Table 3a	4	New robust detail E-WT-4 added with acceptable combinations.
Table 3a	4	New robust detail E-FC-12 added with acceptable combinations.
Table 3b	5	New robust detail E-WT-4 added with relevant notes.
Table 3c	6	New robust detail E-WT-4 added with relevant notes.
Table 4	7	New robust detail E-WT-4 added with relevant notes.
Table 5	7	New robust detail E-FC-12 added with relevant notes.
Table 6	8	New robust details E-WM-19 and E-WT-4 added with relevant notes.
Table 7	8	New robust detail E-FC-12 added with relevant notes.

Separating Wall – Masonry

E-WM-8

Hollow or cellular blocks	1	Besblock Star Performer cellular block added as alternative to solid concrete blocks.
Diagram 1	2	Besblock Star Performer cellular block added as an alternative to inner leaf.
Diagram 2	2	Besblock Star Performer cellular block added as an alternative to inner leaf.
Checklist	8	Besblock Star Performer notes added to point 3.

E-WM-11

1	“Nominated hollow or cellular blocks” added to description.
---	---

E-WM-19

All	1-8	New robust detail added – Dense or lightweight aggregate or Besblock Star Performer cellular block with MONARFLOOR® BRIDGESTOP® and minimum 100mm cavity.
-----	-----	---

Separating Wall – Timber

E-WT-4

All	1-8	New robust detail added – Timber frame separating wall with sheathing, and insulated using Excel Industries’ Warmcel 500.
-----	-----	---

Separating Floor – Concrete

E-FC-12

All	1-6	New robust detail added – Floating screed applied to Thermal Economics IsoRubber Base HP3 on 200mm precast planks.
-----	-----	--

Appendix B

Glossary	2	New definition added for ‘Proprietary screed’.
----------	---	--